




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04B 7/005, H04Q 7/32</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/36382</b> (43) International Publication Date: <b>2 October 1997 (02.10.97)</b>
(21) International Application Number: <b>PCT/GB97/00864</b> (22) International Filing Date: <b>26 March 1997 (26.03.97)</b> (30) Priority Data: 9606269.0                      26 March 1996 (26.03.96)                      GB (71) Applicant (for all designated States except US): <b>MAXON SYSTEMS INC. (LONDON) LTD. [GB/GB];</b> Maxon House, Honeycrook Lane, Salfords, Redhill, Surrey RH1 5JP (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): <b>BALDRY, Francis, William [GB/GB];</b> Maxon Systems Inc. (London) Limited, Maxon House, Honeycrook Lane, Salfords, Redhill, Surrey RH1 5JP (GB). (74) Agent: <b>SHINDLER, Nigel; Batchellor, Kirk &amp; Co.,</b> 2 Pear Tree Court, London EC1R 0DS (GB).		(81) Designated States: <b>CN, DE, GB, JP, KR, US,</b> European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>

(54) Title: CDMA POWER CONTROL



## (57) Abstract

A power control system for a CDMA cellular telephone system comprising means for generating a first signal (14) representing received signal strength; means for generating a second signal (20) representing transmitted signal strength; comparator means (21) for generating an error signal (25) from the difference of the first and second signals; and gain control means (18) for adjusting the transmitted signal strength in accordance with the error signal until the first and second signals are equal.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

"CDMA Power Control"

This invention relates to power control in a spread spectrum code division multiple access cellular telephone system (TIA:IS-95). Such systems normally employ so-called "open loop" and "closed loop" power control.

Open loop power control requires that the automatic gain control stages in the receiver and transmitter of the mobile should track, i.e. for every 1dB increase in the receiver input level, the transmitter output level should decrease by 1dB and vice versa. Since the dynamic range of the AGC system is some 80dB, this is quite difficult to achieve, especially over a range of temperatures.

Closed loop power control requires the mobile transmitter to increment or decrement the output level in 1dB steps in response to commands from the base station.

Normally open and closed loop AGC systems are implemented either by relatively simple variable gain/attenuation devices in the RX and TX chains which require extensive calibration, or sophisticated temperature compensated variable gain MMICs which still require (simpler) calibration.

The present invention seeks to provide a power control system which can utilise readily available and cheap analogue cellular components and which is inherently self

calibrating.

Accordingly the present invention provides a power control system for a CDMA cellular telephone system comprising means for generating a first signal representing received signal strength; means for generating a second signal representing transmitted signal strength; comparator means for generating an error signal from the difference of the first and second signals; and gain control means for adjusting the transmitted signal strength in accordance with the error signal until the first and second signals are equal.

Preferably, gain control means are provided for the received signal input, by comparing the output of the means for generating the first signal, with a reference level, and adjusting the gain until they are equal.

Preferably, the output from the second signal generating means is also modified by a closed loop power control signal, before it is supplied to the comparator.

↓ A preferred form of the present invention therefore provides a power control system for a CDMA cellular telephone system comprising means for supplying the received (RX) CDMA signal to the input of a RX-AGC circuit which is arranged to provide a constant level input for RX-A/D converters by setting the gain to be inversely proportional to the received signal level; means for tapping off the RX-AGC output, and means for filtering the tapped-off signal to reject possible interfering signals and to generate a first

- 3 -

received signal strength voltage (RSSI 1); means for supplying the received CDMA signal to the input of a transmit (TX) AGC; means for generating a second received signal strength voltage (RSSI 2) from the output of the TX-AGC; means for comparing the first and second RSSI voltages and producing a difference signal which is used to adjust the TX-AGC until the RSSI voltages are equal.

Preferably, the second RSSI voltage is also summed with a closed loop power control signal so as to increment or decrement the TX output in response to commands from a base station.

One embodiment of the invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 is a block diagram of the overall arrangement of the circuitry;

Figure 2 is a schematic diagram of an AGC amplifier.

The received CDMA signal (2) is downconverted to an IF and passes through an RX-AGC amplifier (4). The gain of the amplifier is adjusted by the AGC system to ensure that the receive A to D converters (6, 8) are driven at a constant level i.e. the gain is inversely proportional to the received power level. The AGC amplifier may for example be a simple circuit using dual gate FETs, the second gate being used for gain control, in a well-known manner. For example, as shown in Figure 2, a dual gate FET 30 is driven by the input signal (32) at gate g2, while an AGC signal

- 4 -

(34) is applied at gate g1 to provide an output (36).

The CDMA cellular system has to coexist with conventional analogue cellular systems which in practice means that there could be strong interfering signals as close as 900 kHz from the wanted CDMA signal which could cause false RX power measurements if there is insufficient filtering. The filtering is normally provided by a SAW filter at the IF and a steep rolloff low pass filter at baseband. Due to the wideband nature of CDMA(+/- 630kHz), significant rejection at 900kHz is difficult to achieve both technically and cheaply.

The CDMA signal is also tapped off and filtered first by a conventional FM IF filter (10). Most FM cellular receivers employ a second Intermediate Frequency of 450 or 455 khz which means that the first IF filter must provide approximately 70db of rejection at +/- 900kHz (the "image" frequency). The signal then passes into an FM IF chip, converted down to a second IF of say 450kHz, filtered further (12) and a receiver signal strength voltage (14) generated which is compared to a reference (15) in a comparator (16) to produce a gain control voltage for the receiver AGC amplifier.

The RX CDMA signal, prior to amplification, is also fed into the TX AGC amplifier (18) (similar circuit to the RX circuit) and the output level measured in a similar FM IF chip producing a second RSSI voltage (20). A closed loop power control voltage is also added (22) to the second RSSI

- 5 -

voltage at a summer (23) to increment or decrement the power level in response to commands from the base station. The gain of the TX AGC amplifier is adjusted (21) using the difference signal (25) of the two RSSI voltages. For a closed loop control voltage (22) input of zero, the gains of the RX and TX AGC stages are equal. In practice, a gain offset is normally required because the TX IF signal level at the input of the TX AGC amplifier (18) is substantially higher than the RX-IF input level to the RX AGC amplifier 4 and thus gain is provided by an amplifier (26). A filter (24) is required at the output of the TX AGC amplifier (18) to prevent the RX IF signal being retransmitted.

Various easily available components may be utilised to construct the circuitry. Many manufacturers offer FM IF receiver devices with an RSSI characteristic which is very stable over temperature. Ideally RSSI-1 and RSSI-2 should have identical characteristics (i.e. slope, intercept and temperature coefficient). Toshiba offer a suitable device, TA31138FN "Dual Mixer and IF Amplifier for Diversity Reception" for a Japanese Digital Cellular system, employing spatial diversity and therefore requiring two matched IF chains, as shown in the data sheet attached hereto as Appendix A.

Many FM IF chips have a highly linear RSSI characteristic. This can be exploited for closed loop power control by adding an adjustment voltage to the output of RSSI-2. The RSSI sensitivity (mV per dB) can be easily

- 6 -


measured during manufacture of the telephone.

The preferred form of the invention has a number of advantages. The 900kHz filtering function is performed by cheap, readily available components.

In dual mode applications (CMDA/AMPS or CDMA/ETACS), the FM SAW filter, IF amplifier-1 and one of the second IF filters (12) can be used for FM demodulation.

The "turn around" performance of the open loop power control or the ability of the RX and TX AGC circuits to track is a direct function of only how well the two FM IF circuits match (the Toshiba device should achieve +/- 1dB over temperature).

Closed loop power control accuracy is a function of the linearity of the FM IF chip circuit only.



SUBSTITUTE SHEET (RULE 26)

## CLAIMS

1. A power control system for a CDMA cellular telephone system comprising means for generating a first signal (14) representing received signal strength; means for generating a second signal (20) representing transmitted signal strength; comparator means (21) for generating an error signal (25) from the difference of the first and second signals; and gain control means (18) for adjusting the transmitted signal strength in accordance with the error signal until the first and second signals are equal.
2. A power control system according to claim 1 further characterised by gain control means (16) for the received signal input, which is adapted to compare the output of the said means for generating the first signal, with a reference level (15), and to adjust the gain until they are equal.
3. A power control system according to claim 1 or claim 2 further characterised by means (23) for modifying the output from the second signal generating means in accordance with a closed loop power control system (22), before it is supplied to the comparator (21).
4. A power control system for a CDMA cellular telephone system comprising means for supplying the received (RX) CDMA signal to the input of a RX-AGC circuit (4) which is

- 9 -

arranged to provide a constant level input for RX-A/D converters by setting the gain to be inversely proportional to the received signal level; means for tapping off the RX-AGC output, and means for filtering the tapped-off signal to reject possible interfering signals and to generate a first received signal strength voltage (RSSI 1); means for supplying the received CDMA signal to the input of a transmit (TX) AGC (18); means for generating a second received signal strength voltage (RSSI 2) from the output of the TX-AGC; and means (21) for comparing the first and second RSSI voltages and producing a difference signal (25) which is used to adjust the TX-AGC (18) until the RSSI voltages are equal.

5. A power control system according to claim 4 in which the second RSSI voltage (RSSI2) is also summed with a closed loop power control signal (22) so as to increment or decrement the TX output in response to commands from a base station.





FIG. 1

2/2

FIG. 2



SUBSTITUTE SHEET (RULE 26)

## INTERNATIONAL SEARCH REPORT

Intern. Application No  
PCT/GB 97/00864

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04B7/005 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04B H04Q H03G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 94 06218 A (ERICSSON TELEFON AB L M) 17 March 1994	1,2
Y	see page 3, line 8 - line 23 see figure 2	3-5
Y	WO 93 07702 A (QUALCOMM INC) 15 April 1993 * abstract * see page 8, line 18 - page 9, line 3 see page 16, line 4 - line 16 see page 25, line 22 - page 26, line 7 see figure 5	3-5

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

11 June 1997

Date of mailing of the international search report

26. 06. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Lopez Marquez, T

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat'l Application No  
PCT/GB 97/00864

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9406218 A	17-03-94	AU 672628 B	10-10-96
		AU 4988393 A	29-03-94
		CN 1086945 A	18-05-94
		EP 0611499 A	24-08-94
		FI 942033 A	04-05-94
		JP 7504077 T	27-04-95
		NZ 255617 A	26-11-96
-----			
WO 9307702 A	15-04-93	US 5267262 A	30-11-93
		AU 654891 B	24-11-94
		AU 3054392 A	03-05-93
		BG 98704 A	31-05-95
		BR 9206606 A	14-11-95
		CA 2120768 A	15-04-93
		EP 0607359 A	27-07-94
		FI 941637 A	08-06-94
		HU 69842 A	28-09-95
		IL 103368 A	19-01-96
		JP 7502631 T	16-03-95
		NO 941264 A	08-06-94
		ZA 9207539 A	07-07-93
-----			